

## BANDED BELTS

### Range

Section	Pitch Length L <sub>p</sub> (mm)
<b>SPZ</b>	500 - 4500
<b>SPA</b>	500 - 7000
<b>SPB</b>	600 - 12500
<b>SPC</b>	1400 - 17500

**Li : Inside Length**

**Le : Effective Length**

**L<sub>p</sub> : Pitch Length**

Section	Size Range	Belt Width (mm)	Thickness (mm)	Pitch (mm)	No. of belts/band	
<b>CLASSICAL</b>	A	Li (inches) 42 - 137	(15.88 x N)- 2.50	10.00	15.88	6
	B	42 - 600	(19.05 x N)- 2.00	13.00	19.05	6
	C	66 - 120	(25.40 x N)- 3.00	16.50	25.40	4
	C	121 - 600	(25.40 x N)- 3.00	16.50	25.40	6
<b>NARROW</b>	3V	Le (inches) 42 - 150	(10.30 x N)- 0.50	10.00	10.30	6
	5V	105 - 175	(17.50 x N)- 1.50	16.50	17.50	6
	5V	176 - 600	(17.50 x N)- 1.50	16.50	17.50	5
	8V	160 - 600	(28.58 x N)- 3.00	25.50	28.58	5
<b>WEDGE</b>	SPC	L <sub>p</sub> (mm) 2700 - 15000	(25.40 x N)- 3.00	20.00	25.40	5